



# DASHMILE LUBTECH

## Product Name:-

**4T 15W-50 SN**

## Product Description:

4T SN 15W-50 provides premium performance and maximum protection in high performance. It is engineered from advanced synthetic technology to better withstand the rpm, high temperatures and shock loading common to extreme applications.

## Application:

Designed to enhance performance protection for modern motorcycles where API SN (and below) and SAE 15W50 recommended. Compatible with all BS VI engines.

## Specifications:

Meets & exceeds API SN, JASO MA2

## Product Benefits:

- Formulated specially for high performance engines.
- Formulation resists viscosity loss
- Maximum horse power.
- Provides maximum protection in extreme temperatures.
- Reduces heat induced engine oil oxidation.
- Maximum protection against excessive friction.

## Specification & Typical properties:

Sr. No.	Tests	UOM	Method	Results
1.	Appearance	----	Visual	Clear & Bright
2.	Crackle Test	----	----	Negative
3.	Density @ 29.5°C	g/cm <sup>3</sup>	ASTM D 4052	0.8533
4.	Colour		ASTM D 1500	L 2.5
5.	Kinematic Viscosity @ 40°C	cSt	ASTM D 445	119.45
6.	Kinematic Viscosity @ 100°C	cSt	ASTM D 445	17.08
7.	Viscosity Index	----	ASTM D 2270	156
8.	Flash Point (COC)	°C	ASTM D 92	230
9.	Pour Point	°C	ASTM D 97	-28
10.	TBN, mg KOH/g	mg KOH/gm	ASTM D2896B	7.80
11.	Foam Stability Test Seq I	ml/ml	ASTM D 892	0/0
	Seq II	ml/ml	ASTM D 892	0/0
	Seq III	ml/ml	ASTM D 892	0/0