



DASHMILE LUBTECH

Product Name:-

4T 20W-40 SL

Product Description:

4T SL 20W-40 is high performance 4 Stroke motorcycle engine oil. This oil is blended from high viscosity index base stocks and contains additives to meet the stated performance standards.

Application:

4T SL 20W-40 is recommended for all kind of Two Wheelers - 4 Stroke Motor Cycle and Scooters. Compatible with all BS VI engines.

Specifications:

Meets & exceeds API SL, JASO MA2

Product Benefits:

- Helps maintain maximum power and acceleration over the lift of the engine
- Enhanced oil life and longer drain period
- Increases fuel economy
- Maintains high order of engine cleanliness
- Exceptional thermal and oxidation stability

Specification & Typical properties:

Sr. No.	Tests	UOM	Method	Results
1.	Appearance	----	Visual	Clear & Bright
2.	Crackle Test	----	----	Negative
3.	Density @ 29.5°C	g/cm ³	ASTM D 4052	0.8467
4.	Colour		ASTM D 1500	L 2.0
5.	Kinematic Viscosity @ 40°C	cSt	ASTM D 445	94.59
6.	Kinematic Viscosity @ 100°C	cSt	ASTM D 445	14.39
7.	Viscosity Index	----	ASTM D 2270	157
8.	Flash Point (COC)	°C	ASTM D 92	219
9.	Pour Point	°C	ASTM D 97	-27
10.	TBN, mg KOH/g	mg KOH/gm	ASTM D2896B	6.40
11.	Foam Stability Test Seq I	ml/ml	ASTM D 892	0/0
	Seq II	ml/ml	ASTM D 892	0/0
	Seq III	ml/ml	ASTM D 892	0/0