



DASHMILE LUBTECH

Product Name:-

20W-40 CF4/SJ

Product Description:

CF-4 20W-40 is diesel engine oil applicable for Euro 1 and Euro 2 emission requirements in stationary and automotive applications trucks, mini trucks, SUVs etc.

Application:

SAE 20W-40 is recommended for all kind of Diesel Engines. Compatible with all BS VI engines.

Specifications:

Meets & exceeds API CF-4 • MB 228.1 • VOLVO VDS

Product Benefits:

- Perfect for high temperature operation in air-cooled or water-cooled diesel engines.
- Provides bearing protection.
- Compatible for both new generation and older engine designs.

Specification & Typical properties:

Sr. No.	Tests	UOM	Method	Results
1.	Appearance	----	Visual	Clear & Bright
2.	Crackle Test	----	----	Negative
3.	Density @ 29.5°C	g/cm ³	ASTM D 4052	0.8509
4.	Colour		ASTM D 1500	L 2.0
5.	Kinematic Viscosity @ 40°C	cSt	ASTM D 445	110.05
6.	Kinematic Viscosity @ 100°C	cSt	ASTM D 445	14.5
7.	Viscosity Index	----	ASTM D 2270	135
8.	Flash Point (COC)	°C	ASTM D 92	215
9.	Pour Point	°C	ASTM D 97	-27
10.	TBN, mg KOH/g	mg KOH/gm	ASTM D2896B	6.00
11.	Foam Stability Test Seq I	ml/ml	ASTM D 892	0/0
	Seq II	ml/ml	ASTM D 892	0/0
	Seq III	ml/ml	ASTM D 892	0/0