



DASHMILE LUBTECH

Product Name:

4T 20W50 API SN FULLY SYNTHETIC

Product Description:

4T SN SAE 20W-50 provides premium performance and maximum protection in high performance. It is engineered from advanced synthetic technology to better withstand the rpm, high temperatures and shock loading common to extreme applications.

Application:

Designed to enhance performance protection for modern motorcycles where API SN (and below) and SAE 20W50 recommended. Compatible with all BS VI engines.

Specifications:

Meets & exceeds API SN, JASO MA2

Product Benefits:

- Formulated specially for high performance engines.
- Formulation resists viscosity loss
- Maximum horse power.
- Provides maximum protection in extreme temperatures.
- Reduces heat induced engine oil oxidation.
- Maximum protection against excessive friction.

Specification & Typical properties:

Sr. No.	Tests	UOM	Method	Results
1.	Appearance	----	Visual	Clear & Bright
2.	Crackle Test	----	----	Negative
3.	Density @ 29.5°C	g/cm ³	ASTM D 4052	0.8533
4.	Colour		ASTM D 1500	L 2.5
5.	Kinematic Viscosity @ 40°C	cSt	ASTM D 445	119.45
6.	Kinematic Viscosity @ 100°C	cSt	ASTM D 445	17.08
7.	Viscosity Index	----	ASTM D 2270	156
8.	Flash Point (COC)	°C	ASTM D 92	230
9.	Pour Point	°C	ASTM D 97	-32
10.	TBN, mg KOH/g	mg KOH/gm	ASTM D2896B	7.80
11.	Foam Stability Test Seq I	ml/ml	ASTM D 892	0/0
	Seq II	ml/ml	ASTM D 892	0/0
	Seq III	ml/ml	ASTM D 892	0/0