



# DASHMILE LUBTECH

## Product Name:-

**EP 75W-90**

## Product Description:

EP 75W-90 GL-5 is synthetic based oil designed for the lubrication of all gear boxes and axles requiring an API GL-5 level and a viscosity of SAE 75W-90.

## Application:

Lubrication of all gear boxes & axles requiring an API GL-5 level and where a viscometrics of 75W-90 is recommended.

## Specifications:

Meets & exceeds API GL-5 • MIL-L-2105 D • ZF-TE-ML-05A, 07A, 16D, 17B, 19B

## Product Benefits:

- Fluid synthetic based multi-grade oil.
- Excellent fuel economy.
- Enhanced low temperature properties.
- Good performance even under Extreme Pressure & varying load conditions.

## Specification & Typical properties:

Sr. No.	Tests	UOM	Method	Results
1.	Appearance	----	Visual	Clear & Bright
2.	Crackle Test	----	----	Negative
3.	Density @ 29.5°C	g/cm <sup>3</sup>	ASTM D 4052	0.8501
4.	Colour		ASTM D 1500	L 0.5
5.	Kinematic Viscosity @ 40°C	cSt	ASTM D 445	100.06
6.	Kinematic Viscosity @ 100°C	cSt	ASTM D 445	15.03
7.	Viscosity Index	----	ASTM D 2270	158
8.	Flash Point (COC)	°C	ASTM D 92	230
9.	Pour Point	°C	ASTM D 97	-40
10.	TAN, mg KOH/g	mg KOH/gm	ASTM D2896B	1.6
11.	Foam Stability Test Seq I	ml/ml	ASTM D 892	0/0
	Seq II	ml/ml	ASTM D 892	0/0
	Seq III	ml/ml	ASTM D 892	0/0