

ATF- TASA

#### **Product Description:**

ATF premium quality transmission oil, blended from high quality solvent refined base stocks, fortified with carefully selected additives, to give good dispersant, oxidation stability, seal compatibility, anti-foam, anticorrosion and anti-wear characteristics.

# **Application:**

Lubrication of synchromesh gears and automatic and power steering units of automobiles and LCVS requiring Type A & Suffix A fluid.

## **Specifications:**

Meets & exceeds • GM TASA, TYPE A, SUFFIX A

#### **Product Benefits:**

- High thermal and oxidation stability.
- Provides excellent power steering transmission, even at low temperature.
- Reduces gear wear. Improves life of transmission & steering system.
- Compatible with various types of seal materials.

### Specification & Typical properties:

Sr. No.	Tests	UOM	Method	Results
1.	Appearance		Visual	Clear & Bright
2.	Crackle Test			Negative
3.	Density @ 29.5°C	g/cm <sup>3</sup>	ASTM D 4052	0.8488
4.	Colour		ASTM D 1500	RED
5.	Kinematic Viscosity @ 40°C	cSt	ASTM D 445	43.10
6.	Kinematic Viscosity @ 100°C	cSt	ASTM D 445	7.43
7.	Viscosity Index		ASTM D 2270	138
8.	Flash Point (COC)	°C	ASTM D 92	210
9.	Pour Point	°C	ASTM D 97	-30
10.	TAN, mg KOH/g	mg KOH/gm	ASTM D2896B	8.0
	Foam Stability Test Seq I	ml/ml	ASTM D 892	0/0
11.	Seq II	ml/ml	ASTM D 892	0/0
	Seq III	ml/ml	ASTM D 892	0/0