

#### **Product Name:-**

#### 10W

### **Product Description:**

10W is a high performance Hydraulic Transmission Oil This product is specifically engineered using an effective balance of ashless dispersants and metallic detergents combined with inhibitors to control oxidation, wear, corrosion and rust.

## **Application:**

Recommended for 10W is used in a wide range of on and off-highway hydraulic applications.

## **Specifications:**

Meets & exceeds API CF.

### **Product Benefits:**

- Clean hydraulic systems
- Less wear especially in vanes and control valves
- Protects against vane sticking
- Extends drain intervals with oil analysis

# Specification & Typical properties:

Sr. No.	Tests	UOM	Method	Results
1.	Appearance		Visual	Clear & Bright
2.	Crackle Test			Negative
3.	Density @ 29.5°C	g/cm <sup>3</sup>	ASTM D 4052	0.848
4.	Colour		ASTM D 1500	L 0.5
5.	Kinematic Viscosity @ 40°C	cSt	ASTM D 445	40
6.	Kinematic Viscosity @ 100°C	cSt	ASTM D 445	6.6
7.	Viscosity Index		ASTM D 2270	118
8.	Flash Point (COC)	°C	ASTM D 92	200
9.	Pour Point	°C	ASTM D 97	-20
10.	TBN, mg KOH/g	mg KOH/gm	ASTM D2896B	4.0
11.	Foam Stability Test Seq I	ml/ml	ASTM D 892	0/0
	Seq II	ml/ml	ASTM D 892	0/0
	Seq III	ml/ml	ASTM D 892	0/0