

Product Description:

4T 15W-50 API SN is a fully synthetic, superior performance 4-stroke competition engine oil. High- performance And Ester Base oil combined with the revolutionary Ester Synthetic additive system guarantee outstanding performance in the following areas: A very powerful lubricating film, even under the most extreme operating conditions Maximum engine performance

Application:

Designed to enhance performance protection for modern motorcycles where API SN (and below) and SAE 15W50 recommended. Suitable for Motorbike Engines.

Specifications:

Meets & exceeds API SN, JASO MA2

Product Benefits:

- Formulated specially for high performance engines.
- Formulation resists viscosity loss
- Maximum horse power.
- Provides maximum protection in extreme temperatures.
- Reduces heat induced engine oil oxidation.
- Maximum protection against excessive friction.

Specification & Typical properties:

Sr. No.	Tests	UOM	Method	Results
1.	Appearance		Visual	Clear & Bright
2.	Crackle Test			Negative
3.	Density @ 29.5°C	g/cm ³	ASTM D 4052	0.8678
4.	Colour		ASTM D 1500	Fluorescent Green
5.	Kinematic Viscosity @ 40°C	cSt	ASTM D 445	119.45
6.	Kinematic Viscosity @ 100°C	cSt	ASTM D 445	17.08
7.	Viscosity Index		ASTM D 2270	156
8.	Flash Point (COC)	°C	ASTM D 92	223
9.	Pour Point	°C	ASTM D 97	-40
10.	TBN, mg KOH/g	mg KOH/gm	ASTM D2896B	7.80
11.	Foam Stability Test Seq I	ml/ml	ASTM D 892	0/0
	Seq II	ml/ml	ASTM D 892	0/0
	Seq III	ml/ml	ASTM D 892	0/0